

Bezeichnung	Artikelnummer	Lichtfarbe	Optik	Systemleistung	Lichtstrom System	Abmessungen
BaseLED 10-585 M2K	96010403009	4000 K	satiniert	10,1 W	1333 lm	585x74x32 mm
BaseLED 15-865 K2K	96013303000	3000 K	klar	13,4 W	2081 lm	865x74x35 mm
BaseLED 15-865 M2K	96013303001	3000 K	klar	13,4 W	2081 lm	865x74x32 mm
BaseLED 15-865 K2K	96013303008	3000 K	satiniert	13,4 W	1888 lm	865x74x35 mm
BaseLED 15-865 M2K	96013303009	3000 K	satiniert	13,4 W	1888 lm	865x74x32 mm
BaseLED 15-865 D2K	96013303016	3000 K	klar	13,4 W	2081 lm	865x74x34 mm
BaseLED 15-865 D2K	96013303017	3000 K	satiniert	13,4 W	1888 lm	865x74x34 mm
BaseLED 15-865 K2K	96013403000	4000 K	klar	13,4 W	2207 lm	865x74x35 mm
BaseLED 15-865 M2K	96013403001	4000 K	klar	13,4 W	2207 lm	865x74x32 mm
BaseLED 15-865 K2K	96013403008	4000 K	satiniert	13,4 W	2002 lm	865x74x35 mm
BaseLED 15-865 M2K	96013403009	4000 K	satiniert	13,4 W	2002 lm	865x74x32 mm
BaseLED 15-865 D2K	96013403016	4000 K	klar	13,4 W	2207 lm	865x74x34 mm
BaseLED 15-865 D2K	96013403017	4000 K	satiniert	13,4 W	2002 lm	865x74x34 mm
BaseLED 15-865 K2K	96013503000	5000 K	klar	13,8 W	2095 lm	865x74x35 mm
BaseLED 15-865 M2K	96013503001	5000 K	klar	13,8 W	2095 lm	865x74x32 mm
BaseLED 15-865 K2K	96013503008	5000 K	satiniert	13,8 W	1901 lm	865x74x35 mm
BaseLED 15-865 M2K	96013503009	5000 K	satiniert	13,8 W	1901 lm	865x74x32 mm
BaseLED 15-865 D2K	96013503016	5000 K	klar	13,8 W	2095 lm	865x74x34 mm
BaseLED 15-865 D2K	96013503017	5000 K	satiniert	13,8 W	1901 lm	865x74x34 mm
BaseLED 19-1145 K2K	96017303000	3000 K	klar	17,2 W	2774 lm	1145x74x35 mm
BaseLED 19-1145 M2K	96017303001	3000 K	klar	17,2 W	2774 lm	1145x74x32 mm
BaseLED 19-1145 K2K	96017303008	3000 K	satiniert	17,2 W	2517 lm	1145x74x35 mm
BaseLED 19-1145 M2K	96017303009	3000 K	satiniert	17,2 W	2517 lm	1145x74x32 mm
BaseLED 19-1145 D2K	96017303016	3000 K	klar	17,2 W	2774 lm	1145x74x34 mm
BaseLED 19-1145 D2K	96017303017	3000 K	satiniert	17,2 W	2517 lm	1145x74x34 mm
BaseLED 19-1145 K2K	96017403000	4000 K	klar	17,2 W	2939 lm	1145x74x35 mm
BaseLED 19-1145 M2K	96017403001	4000 K	klar	17,2 W	2939 lm	1145x74x32 mm
BaseLED 19-1145 K2K	96017403008	4000 K	satiniert	17,2 W	2666 lm	1145x74x35 mm
BaseLED 19-1145 M2K	96017403009	4000 K	satiniert	17,2 W	2666 lm	1145x74x32 mm
BaseLED 19-1145 D2K	96017403016	4000 K	klar	17,2 W	2939 lm	1145x74x34 mm
BaseLED 19-1145 D2K	96017403017	4000 K	satiniert	17,2 W	2666 lm	1145x74x34 mm
BaseLED 19-1145 K2K	96017503000	5000 K	klar	17,7 W	2794 lm	1145x74x35 mm
BaseLED 19-1145 M2K	96017503001	5000 K	klar	17,7 W	2794 lm	1145x74x32 mm
BaseLED 19-1145 K2K	96017503008	5000 K	satiniert	17,7 W	2534 lm	1145x74x35 mm
BaseLED 19-1145 M2K	96017503009	5000 K	satiniert	17,7 W	2534 lm	1145x74x32 mm
BaseLED 19-1145 D2K	96017503016	5000 K	klar	17,7 W	2794 lm	1145x74x34 mm
BaseLED 19-1145 D2K	96017503017	5000 K	satiniert	17,7 W	2534 lm	1145x74x34 mm
BaseLED 23-1425 K2K	96022303000	3000 K	klar	20,9 W	3468 lm	1425x74x35 mm
BaseLED 23-1425 M2K	96022303001	3000 K	klar	20,9 W	3468 lm	1425x74x32 mm
BaseLED 23-1425 K2K	96022303008	3000 K	satiniert	20,9 W	3146 lm	1425x74x35 mm
BaseLED 23-1425 M2K	96022303009	3000 K	satiniert	20,9 W	3146 lm	1425x74x32 mm
BaseLED 23-1425 D2K	96022303016	3000 K	klar	20,9 W	3468 lm	1425x74x34 mm
BaseLED 23-1425 D2K	96022303017	3000 K	satiniert	20,9 W	3146 lm	1425x74x34 mm
BaseLED 23-1425 K2K	96022403000	4000 K	klar	20,9 W	3676 lm	1425x74x35 mm
BaseLED 23-1425 M2K	96022403001	4000 K	klar	20,9 W	3676 lm	1425x74x32 mm

BaseLED 23-1425 K2K	96022403008	4000 K	satiniert	20,9 W	3335 lm	1425x74x35 mm
BaseLED 23-1425 M2K	96022403009	4000 K	satiniert	20,9 W	3335 lm	1425x74x32 mm
BaseLED 23-1425 D2K	96022403016	4000 K	klar	20,9 W	3676 lm	1425x74x34 mm
BaseLED 23-1425 D2K	96022403017	4000 K	satiniert	20,9 W	3335 lm	1425x74x34 mm
BaseLED 23-1425 K2K	96022503000	5000 K	klar	21,6 W	3492 lm	1425x74x35 mm
BaseLED 23-1425 M2K	96022503001	5000 K	klar	21,6 W	3492 lm	1425x74x32 mm
BaseLED 23-1425 K2K	96022503008	5000 K	satiniert	21,6 W	3168 lm	1425x74x35 mm
BaseLED 23-1425 M2K	96022503009	5000 K	satiniert	21,6 W	3168 lm	1425x74x32 mm
BaseLED 23-1425 D2K	96022503016	5000 K	klar	21,6 W	3492 lm	1425x74x34 mm
BaseLED 23-1425 D2K	96022503017	5000 K	satiniert	21,6 W	3168 lm	1425x74x34 mm