

Bezeichnung	Artikelnummer	Lichtfarbe	Optik	Systemleistung	Lichtstrom System	Polzahl	Abmessungen
InduLED 23-1798 S	73923400020	4000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400023	4000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400025	4000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400600	4000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400603	4000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400605	4000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400900	4000 K	110°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400903	4000 K	110°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923400905	4000 K	110°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500020	5000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500023	5000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500025	5000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500600	5000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500603	5000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500605	5000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500900	5000 K	110°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500903	5000 K	110°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	73923500905	5000 K	110°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	75923400020	4000 K	High Rack	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400023	4000 K	High Rack	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400025	4000 K	High Rack	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400600	4000 K	60°	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400603	4000 K	60°	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400605	4000 K	60°	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400900	4000 K	110°	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400903	4000 K	110°	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923400905	4000 K	110°	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923500020	5000 K	High Rack	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923500023	5000 K	High Rack	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	75923500025	5000 K	High Rack	23,2 W	4167 lm	5-polig	1798x71x106 mm
InduLED 23-1798 S	76213114282	4000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	76309222271	4000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	76405330259	4000 K	High Rack	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	76501438247	4000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	76597546236	4000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 23-1798 S	76693654224	4000 K	60°	23,2 W	4167 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400020	4000 K	High Rack	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400023	4000 K	High Rack	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400025	4000 K	High Rack	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400600	4000 K	60°	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400603	4000 K	60°	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400605	4000 K	60°	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400900	4000 K	110°	26,6 W	4814 lm	3-polig	1798x71x106 mm
InduLED 26-1798 S	73926400903	4000 K	110°	26,6 W	4814 lm	3-polig	1798x71x106 mm









InduLED 69-1798 S	73969500600	5000 K	60°	68,9 W	11471 lm	3-polig	1798x71x106 mm
InduLED 69-1798 S	73969500603	5000 K	60°	68,9 W	11471 lm	3-polig	1798x71x106 mm
InduLED 69-1798 S	73969500605	5000 K	60°	68,9 W	11471 lm	3-polig	1798x71x106 mm
InduLED 69-1798 S	73969500900	5000 K	110°	68,9 W	11471 lm	3-polig	1798x71x106 mm
InduLED 69-1798 S	73969500903	5000 K	110°	68,9 W	11471 lm	3-polig	1798x71x106 mm
InduLED 69-1798 S	73969500905	5000 K	110°	68,9 W	11471 lm	3-polig	1798x71x106 mm
InduLED 69-1798 S	75969400020	4000 K	High Rack	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400023	4000 K	High Rack	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400025	4000 K	High Rack	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400600	4000 K	60°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400603	4000 K	60°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400605	4000 K	60°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400900	4000 K	110°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400903	4000 K	110°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969400905	4000 K	110°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500020	5000 K	High Rack	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500023	5000 K	High Rack	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500025	5000 K	High Rack	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500600	5000 K	60°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500603	5000 K	60°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500605	5000 K	60°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500900	5000 K	110°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500903	5000 K	110°	68,9 W	11471 lm	5-polig	1798x71x106 mm
InduLED 69-1798 S	75969500905	5000 K	110°	68,9 W	11471 lm	5-polig	1798x71x106 mm